

کمپانی VÖLKL تولید کننده کفش و چکمه با رعایت بالاترین استانداردهای ایمنی است. برای ساخت کفش های ایمنی و چکمه های تخصصی این کمپانی سعی شده تا راحتی و ایمنی همزمان در نظر گرفته شود. نشان "ساخت آلمان" کیفیت محصولات VÖLKL را گارانتی می کند. تعهد و تجربه VÖLKL باعث شده است که محصولات تولیدی این کمپانی، رضایت مندی مشتریان را به دنبال داشته باشد و این گویای طراحی حساب شده و استفاده از بهترین مواد اولیه است.

Kommandant Pro

Réf.: 33012 | Pointures: 50-36 | DIN EN ISO 15090:2012



Overview

- quick entry and perfect fit
- award winning model
- injection moulded rubber/PU sole with excellent energy absorption and heat insulation properties
- temperature inside the shoe increases by only 2.3+ °C
- proportion of PU above %90
- new and recyclable Sympatex® Moisture-Tec® membrane lining

improved comfort thanks to flex points on instep and upper heel | forepart and upper leg padding, with additional ankle padding | glove friendly pull-on loops | wide natural fit in size 12 | leg height about 33 cm | weight approx. 1250 g | black, full grain waterproof leather 2.6-2.4mm | no side seams | anatomically shaped steel toe cap | abrasion resistant scuff cap with twin recessed seams | removable, anatomically shaped and sweat absorbing cork insole

- self-cleaning outsole with tread depth of 6mm | lateral profile | stainless steel midsole | oil, fuel and acid resistant | slipping resistance SRC
- breathable and waterproof | improved foot climate (%74 less moisture) and reduced heat accumulation (%45 less heat) compared to leading market technologies

Technical Description



Leutnant Pro

Reference: 33013 | Sizes 50-36 | EN ISO 15090:2012



Overview

- injection moulded rubber/PU sole with excellent energy absorption and heat insulation properties
- temperature inside the shoe increases by only 2.3+ °C
- proportion of PU above %90
- upper construction with 3D-mesh-lining
- no heat accumulation and pleasant foot environment
- improved air circulation
- insulation against cold and heat
- comfortable padding
- high safety for an unbeatable price

- self-cleaning outsole with tread depth of 6mm | lateral profile | oil, fuel and acid resistant | slipping resistance SRC
- handy pull on loops | wide natural fit in size 12 | leg height about 31 cm | weight approx. 1050 g | black, full grain waterproof leather | no side seams | pre formed and reinforced counter | removable, anatomically shaped and sweat absorbing cork insole
- ankle padding and 3D-mesh-lining
- heat resistant threads (Nomex) | reflective straps on front and back | anatomically shaped steel toe cap, impact resistant up to 200 joules | abrasion resistant scuff cap with twin recessed seams | stainless steel midsole

Technical Description

One CS Lacing boots

Reference: 33330 | Sizes 50-36 | EN ISO 15090:2012 | DIN EN ISO 17249:2014



Overview

- innovative VÖLKL® 3step-Comfort-System for more flexibility, comfort and durability
- glove friendly and quick entry thanks to specially developed gripping sections on each side
- flexible and dividable zip system
 - easy care and cleaning
- injection moulded rubber/PU sole with excellent energy absorption and heat insulation properties
 - temperature inside the shoe increases by only 2.3+ °C
 - proportion of PU above %90
- new and recyclable Sympatex® Moisture-Tec® membrane lining

Technical Description

- cut protection class 3 | wide natural fit in size 12 | leg height about 29 cm | weight approx. 1280 g | black, full grain waterproof leather 2.6-2.4mm | no side seams | anatomically shaped steel toe cap | abrasion resistant scuff cap with twin recessed seams | removable, anatomically shaped and sweat absorbing cork insole
- pull-on loops on each side | quick entry lacing system (Nomex) with emergency opener
- completely dividable and movable metallic zip | removable slider with leather grip
- self-cleaning outsole with tread depth of 6mm | lateral profile | stainless steel midsole | oil, fuel and acid resistant | slipping resistance SRC
- breathable and waterproof | improved foot climate (%74 less moisture) and reduced heat accumulation (%45 less heat) compared to leading market technologies



Primus 21 ESD Lacing boot

Reference: 33323E | Sizes 50-36 | EN ISO 15090:2012 F2A AN CI HI3 SRC



Overview

- injection moulded rubber/PU sole with excellent energy absorption and heat insulation properties
 - temperature inside the shoe increases by only 2.3+ °C
 - proportion of PU above %90
- flexible and dividable zip system
 - no pressure on inStep
 - easy care and cleaning
- new and recyclable Sympatex® Moisture-Tec® membrane lining
 - water resistant boots that will always keep your feet dry
- Intelligent use of reinforcing materials in the upper
 - form, entry and stability remain the same, even after years of use

Technical description

- self-cleaning outsole with tread depth of 6mm | lateral profile | stainless steel midsole | oil, fuel and acid resistant | slipping resistance SRC
- quick entry lacing system (Nomex) with emergency opener | dividable and movable metallic zip | removable slider with leather grip
- breathable and waterproof | improved foot climate (%78 less moisture) and reduced heat accumulation (%45 less heat) compared to leading market technologies
- leg height about 23 cm | weight approx. 1150 g | black, full grain waterproof leather 2.6-2.4mm | no side seams | anatomically shaped steel toe cap | abrasion resistant scuff cap with twin recessed seams | removable, anatomically shaped and sweat absorbing cork insole | heat resistant thread (Nomex), reflective back strap and side panels | anatomically shaped ankle bone, tongue and forepart padding | flex point on upper heel | pull-on loops at the rear of the boot | preformed and reinforced counter | classified as dissipative footwear (ESD class 3-1 DIN EN 3:2002-4-61340)



VÖLKL
PROFESSIONAL



۸۸۸۷۰۳۴۴ - ۸۸۷۹۱۹۳۶
www.khalileng.com

تهران | بلوار نلسون ماندلا | خیابان وحید
دستگردی | شماره ۲۶۵ | برج پیم | طبقه ۱۱
واحد ۶ | آکد پستی: ۱۹۶۸۶۳۴۳۱۴



شرکت مهندسی و بازرگانی خلیل